Regeneration for reverse-osmosis membranes

L20 ANSWER 51 OF 121 HCA COPYRIGHT 2002 ACS

AN 85:166227 HCA

IN Tsukamoto, Kiyoshi

PA Ebara-Infilco Co., Ltd., Japan

SO Japan. Kokai, 5 pp. CODEN: JKXXAF

DT Patent

LA Japanese

FAN.CNT 1

ΡI

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 51071880 JP 55037283	A2 B4	19760622 . 19800926	JP 1974-145988	19741219

AB An inorg. or org. compd. contg. soln. is fed into the solute side of a spent membrane and pressurized to transfer the solvent through the membrane. Then a gas or liq. is passed through the unit, and the membrane is treated with enzymatic agent (A) and complexing agent (B) or chelating agent (C). Optionally, A follows B and/or C. The regeneration is achieved simply and efficiently. Thus, a membrane, used 500 hr, was flushed with deionized water, a soln. (pH 3.5) contg. (B) EDTA [60-00-4] 0.4 and citric acid [77-92-9] 0.2% was circulated in the cell at 0.6 kg/cm2, then N was replaced with deionized water, and this processes were repeated 3 times. An air-B mixt. was circulated in the cell at 0.4-0.5 kg/cm2 for .apprx.15 sec, then the pressure was redued to 0 kg/cm2. This process was repeated 10 times. After treatment, the membrane had 97% of its original permeability to tap water.

Sopheon/Teltech Research Services

Membrane Cleaning Technologies

© 2001 Sopheon Corporation. All rights reserved

April 4, 2002